


铺路机链

Paver machine chains



ISO/DIN 链号ISO/DIN Chain No.	节距 Pitch	滚子直径 Roller diameter	内节内宽 Width between inner plates	销轴直径 Pin diameter	销轴长度 Pin length	链板高度 plate depth	链板厚度 Plate thickness	抗拉强度 Ultimate tensile strength	平均抗拉强度 Average tensile strength
	P	d ₁ max	b ₁ min	d ₂ max	L max	h ₂ max	T	Q min	Q ₀
	mm	mm	mm	mm	mm	mm	mm	kN	kN
SS40SL	78.11	31.75	31.75	15.90	89.65	38.00	9.50	265.60	300.00

横梁与链条装配尺寸:

代号	A	D	B	代号	A	D	B
SS40SL-141-00	113	424.66	542.93	SS40SL -152-00	100	278.61	396.88
SS40SL -142-00	98	424.66	542.93	SS40SL -153-00	103	381.79	500.06
SS40SL -143-00	103	424.66	542.93	SS40SL -154-00	89	424.66	542.93
SS40SL-144-00	88	381.79	500.06	SS40SL -155-00	104	278.61	396.88
SS40SL -145-00	116	570.71	688.98	SS40SL -156-00	102	424.66	542.93
SS40SL -146-00	111	470.69	588.96	SS40SL -157-00	111	381.79	500.06
SS40SL -147-00	96	470.69	588.96	SS40SL -158-00	108	381.79	500.06
SS40SL -148-00	86	424.66	542.93	SS40SL -159-00	108	468.31	586.58
SS40SL -149-00	81	424.66	542.93	SS40SL -160-00	116	468.31	586.58
SS40SL -150-00	97	424.66	542.93	SS40SL -175-00	107	381.79	500.06
SS40SL -151-00	87	348.46	466.73	SS40SL -176-00	100	424.66	542.93